



CABLE SELECTION CHART

HP	SUBMERSIBLE PUMPSET CABLE SELECTION CHART FOR 415 V, 3 PHASE -50 HZ.													
	LENGTH IN METERS (3 CORE SUBMERSABLE FLAT CABLE)													
	10	20	30	40	50	60	70	80	90	100	120	140	160	
1.0/1.5	1.00	1.00	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	2.50	2.50	
3.0	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	2.50	2.50	2.50	2.50	2.50	
4.0	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	2.50	2.50	2.50	2.50	2.50	
5.0	2.50	2.50	2.50	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	
6.0	2.50	2.50	2.50	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	
7.5 S	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	6.00	6.00	6.00	6.00	6.00	
10.0	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	10.00	10.00	10.00	
12.5	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	10.00	10.00	10.00	10.00	10.00	
15.0	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	16.00	16.00	16.00	16.00	16.00	
17.5	10.00	10.00	10.00	10.00	10.00	10.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00	
20.0	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00	25.00	25.00	25.00	25.00	
25.0	16.00	16.00	16.00	16.00	16.00	16.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	
30.0	16.00	16.00	16.00	16.00	16.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	
40.0	16.00	16.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	
50.0	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	25.00	

GENERAL INFORMATION

- Prices of model not mentioned here in will be furnished on request if found technically viable.
- Order will be accepted on receipt of advance payment.
- GST will be charge extra as applicable at the time of dispatch.
- Freight and insurance to be borne by Buyer.
- Company has right to revise the pricelist and include/withdraw and model
- It is recommended to select the pumpset within a highlighted working zone Images, Design, MOC and discharge Date indicated in this booklet are for general information and many different with supplied models due to site condition and continuois upgradation.
- V3, V4, V5, V6, V6/7, V6/7, V6/8, V8, Performance characteristic cum price list is effective
Customer are advised to use quality accessories, panels and cable etc. of appropriate values.
All disputes subject to Gandhinagar jurisdiction.

